

Noble Charlie Yester — Rig Specifications



Noble Charlie Yester

Capacities

Quarters	90
Variable Load	5,191 kips
Mud Cement Bulk	8,100 cu ft
LiquidMud	1,737 bbls
Fuel	3,120 bbls
DrillWater	5,300 bbls
PotableWater	1,283 bbls

General

Rig Type	Jackup
Rig Design	Marathon LeTourneau 116-C
Built By	Marathon LeTourneau, Singapore
Year Constructed	1980
Water Depth Minimum	25
Water Depth Rated	300
Drilling Depth	25,000 ft
Hull Dimensions	243' x 200' x 26'
Spud Diameter	46'
Leg Length	410'
Cantilever Length	52'
Drill Pattern	52' x 24'
Draft, Transit	14.93'

Heliport

Sikorsky S61N

Equipment

Drawworks	National Oilwell 1625 DE; 3,000 hp
Pumps	(2) National Oilwell 12-P-160; 1,600 hp
Total HP	5,550
Hook Load	1,000,000 lbs
Max Load	1,250 kips
Top Drive	Varco TDS-3H
Derrick	160' x 30' x 30'
Bop System	(1) Cameron "U" Double 13-5/8" x 10,000 psi (1) Cameron "U" Single 13-5/8" x 10,000 psi (1) Hydril 13-5/8" x 5,000 psi Annular
Cranes	(3) Marathon LeTourneau PCM-120-AS, (1) National OS 105
Mud Cleaner	
Shakers	(1) Brandt Dual Tandem Scalper, (3) Derrick L48