

# Noble Ed Holt — Rig Specifications



Noble Ed Holt

## Capacities

Quarters	84
Variable Load	3,600 kips
Mud Cement Bulk	6,780 cu ft
LiquidMud	2,055 bbls
Fuel	4,872 bbls
DrillWater	5,670 bbls
PotableWater	1,561 bbls

## General

Rig Type	Jackup
Rig Design	Livingston Class 111-C
Built By	Livingston Shipbuilding Co., Orange, Texas
Year Constructed	1981; 2003
Water Depth Minimum	30
Water Depth Rated	300
Drilling Depth	25,000 ft
Hull Dimensions	200' x 186' x 22'
Spud Diameter	48.00'
Leg Length	414'
Cantilever Length	45'
Drill Pattern	45' x 24'
Draft, Transit	21.5'

## Heliport

Sikorsky S61N

## Equipment

Drawworks	National Oilwell E-3000; 3,000 hp
Pumps	(2) National Oilwell A-1700-PT; 1,600 hp
Total HP	5,850
Hook Load	1,230,000 lbs
Max Load	1,000 kips
Top Drive	Varco TDS-4SH
Derrick	160' x 30' x 30'
Bop System	(1) Cameron 13-5/8" 10,000 psi double ram; (1) Cameron 13-5/8" 10,000 psi single ram; (1) Hydril 13 5/8" 5,000 psi annular
Cranes	(2) FMC Link Belt ABS -218A. 120' Booms. 31st at 40' Radius
Mud Cleaner	Demco 4M16 Desilter over Brandt LCM 2D Linear Moti
Shakers	(3) Brandt scalpers over (3) Triton NNF 1000